

Your nearest Merlo dealer

MERLO

TRE EMME
MERLO GROUP

MERLO S.P.A.

Via Nazionale, 9 - 12010 S. Def. di Cervasca - Cuneo - Italia

Tel. +39 0171 614111 - Fax +39 0171 684101

www.merlo.com - info@merlo.com

STABILIZED TELEHANDLERS	P30.10	P35.11	TF35.11TT-145	P40.12	P40.12PLUS	P40.13	P40.13PLUS	P40.13CSTOP	P40.14	P40.14PLUS	P40.14CSTOP	P40.17	P40.17PLUS	P40.17CSTOP	P50.18PLUS	P50.18CSTOP
Max. capacity (kg)	3000	3500	3500	4000	4000	4000	4000	4000	4000	4000	4000	4000	4000	4000	5000	5000
Lifting height (m)	9,8	11	11	11,5	11,5	12,5	12,5	12,5	13,5	13,5	13,5	16,6	16,6	16,6	17,5	17,5
Operating weight (kg)	7600	9000	9100	9200	9200	9300	9300	9650	9950	9950	10300	11670	11670	12020	13300	13650
Standard tires	400/70-20	400/70-24	400/70-24	400/70-20	400/70-20	400/70-20	400/70-20	400/70-20	400/70-20	400/70-20	400/70-20	400/70-24	400/70-24	400/70-24	400/80-24	400/80-24
Width (mm)	2100	2310	2310	2240	2240	2240	2240	2240	2240	2240	2240	2420	2420	2420	2480	2480
Height (mm)	2120 (2020 L)	2530	2530	2425	2425	2425	2425	2425	2425	2425	2425	2500	2500	2500	2535	2535
Length (mm)	4700	5150	5150	5010	5010	5410	5410	5410	5750	5750	5750	5970	5970	5970	6190	6190
Boom side shift (mm)	-	+/- 310	+/- 310	+/- 330	+/- 330	+/- 340	+/- 340	+/- 340	+/- 345	+/- 345	+/- 345	+/- 435	+/- 435	+/- 435	+/- 445	+/- 445
Frame levelling (%)	-	+/- 8	+/- 8	+/- 8	+/- 8	+/- 8	+/- 8	+/- 8	+/- 8	+/- 8	+/- 8	+/- 8	+/- 8	+/- 8	+/- 8	+/- 8
Engine	Kohler Z504 TCR	Kohler Z504 TCR	Deutz TCD3.6	Kohler KDI2504	Perkins 904J	Kohler KDI2504	Perkins 904J	Perkins 904J	Kohler KDI2504	Perkins 904J	Perkins 904J	Kohler KDI2504	Perkins 904J	Perkins 904J	Perkins 904J	Perkins 904J
Stage V	DOC+DPF	DOC+DPF	SCR + DPF + DOC	DOC+DPF	SCR+DPF+DOC	DOC + DPF	SCR+DPF+DOC	SCR+DPF+DOC	DOC+DPF	SCR+DPF+DOC	SCR+DPF+DOC	DOC+DPF	SCR+DPF+DOC	SCR+DPF+DOC	SCR+DPF+DOC	SCR+DPF+DOC
Displacement/Cylinders	2500/4	2500/4	3600/4	2500/4	3600/4	2500/4	3600/4	3600/4	2500/4	3600/4	3600/4	2500/4	3600/4	3600/4	3600/4	3600/4
Engine power (kW/HP)	55,4/75,1	55,4/75,1	105/143	55,4/75,1	85,9/115	55,4/75,1	85,9/115	85,9/115	55,4/75,1	85,9/115	85,9/115	55,4/75,1	85,9/115	85,9/115	85,9/115	85,9/115
EPD	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
Number of speed	2	2	2	2	2	2	2	TOP-2V	2	2	TOP-2V	2	2	TOP-2V	2	TOP-2V
Max. speed (km/h)	40	33	40	33	40	33	40	40	33	40	40	33	40	40	40	40
Hydraulic pump	LS+FS	LS+FS	LS+FS	LS	LS	LS	LS	LS+FS	LS	LS+FS	LS	LS	LS	LS+FS	LS	LS+FS
Flow/pressure (l/min - bar)	117-210	117-250	150-250	104-250	104-250	104-250	104-250	145-250	104-250	104-250	145-250	104-250	104-250	145-250	104-250	145-250
ASCS	Light	Light	Light	Light	Full	Light	Full	Full	Light	Full	Full	Light	Full	Full	Full	Full
ROPS - FOPS level II	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
Cab suspension	-	-	-	-	-	-	-	●	-	-	●	-	-	●	-	●

HIGH CAPACITY TELEHANDLERS	P72.10PLUS	P50.18HM	P65.14HM	P120.10HM	TF45.11T-170-HF	TF45.11TCS-170-HF	TF45.11TCS-170 CVTRONIC-HF	TF50.8T-170-HF	TF50.8TCS-170-HF	TF50.8TCS-170 CVTRONIC-HF	TF65.9T-170-HF	TF65.9TCS-170-HF	TF65.9TCS-170 CVTRONIC-HF
Max. capacity (kg)	7200	5000	6500	12000	4500	4500	4500	5000	5000	5000	6500	6500	6500
Lifting height (m)	9,55	17,9	13,9	9,8	10,6	10,6	10,6	7,8	7,8	7,8	8,8	8,8	8,8
Operating weight (kg)	11300	15700	15250	16200	9850	10000	10050	9500	9700	9750	11000	11200	11250
Standard tires	400/70-24	17,5-25	17,5-25	17,5-25	500/70-24	500/70-24	500/70-24	500/70-24	500/70-24	500/70-24	500/70R24	500/70R24	500/70R24
Width (mm)	2240	2520	2520	2520	2400	2400	2400	2400	2400	2400	2400	2400	2400
Height (mm)	2500	2850	2850	2850	2530	2590	2590	2530	2590	2590	2510	2510	2510
Length (mm)	5480	6180	5910	5770	5040	5040	5040	4870	4870	4870	5260	5260	5260
Boom side shift (mm)	+/- 250	+/- 440	+/- 375	+/- 185	-	-	-	-	-	-	-	-	-
Frame levelling (%)	+/- 8	+/- 8	+/- 8	+/- 8	+/- 8	+/- 8	+/- 8	+/- 8	+/- 8	+/- 8	+/- 8	+/- 8	+/- 8
Engine	Perkins 904J	FPT NEF45	FPT NEF45	FPT NEF45	FPT NEF45	FPT NEF45	FPT NEF45	FPT NEF45	FPT NEF45	FPT NEF45	FPT NEF45	FPT NEF45	FPT NEF45
Stage V	SCR+DPF+DOC	SCR+DPF+DOC	SCR+DPF+DOC	SCR+DPF+DOC	SCR+DPF+DOC	SCR+DPF+DOC	SCR+DPF+DOC	SCR+DPF+DOC	SCR+DPF+DOC	SCR+DPF+DOC	SCR+DPF+DOC	SCR+DPF+DOC	SCR+DPF+DOC
Displacement/Cylinders	3600/4	4500/4	4500/4	4500/4	4500/4	4500/4	4500/4	4500/4	4500/4	4500/4	4500/4	4500/4	4500/4
Engine power (kW/HP)	85,9/115	125/170	125/170	125/170	125/170	125/170	125/170	125/170	125/170	125/170	125/170	125/170	125/170
EPD	●	●	●	●	●	●	●	●	●	●	●	●	●
Number of speed	2	CVTronic	CVTronic	CVTronic	2	2	CVTronic	2	2	CVTronic	2	2	CVTronic
Max. speed (km/h)	40	40	40	40	40	40	40	40	40	40	40	40	40
Hydraulic pump	LS	LS+FS	LS+FS	LS+FS	HF	HF	HF	HF	HF	HF	HF	HF	HF
Flow / pressure (l/min - bar)	104 - 250	158 - 210	158 - 210	158 - 210	160 - 250	160 - 250	160 - 250	160 - 250	160 - 250	160 - 250	160 - 250	160 - 250	160 - 250
ASCS	Full	Full	Full	Full	Full	Full	Full	Full	Full	Full	Full	Full	Full
ROPS - FOPS level II	●	●	●	●	●	●	●	●	●	●	●	●	●
Cab suspension	-	-	-	-	-	-	●	-	-	●	-	-	●

TOOL-HANDLER TRACTORS	MM135MC	MM135MCCS	MM160MCCS	MM250X	MM350X
Engine	Deutz Stage IV, SCR+DPF	Deutz Stage IV, SCR+DPF	Deutz Stage IV, SCR+DPF	Deutz Stage V	Deutz Stage V
Displacement/Cylinders	3600 / 4	3600 / 4	4100 / 4	6100 / 6	7500 / 6
Engine power (kW/HP)	100 - 136	100 - 136	115 - 156	180-241	180-250
Hydrostatic transmission	●	●	●	●	●
Number of speed	2	2	2	2 + 1	2 + 1
Max. speed (km/h)	40	40	40	40	40
Epicyclic reducers	●	●	●	●	●
4WD and 4 steering wheel	●	●	●	●	●
Cab suspension	-	●	●	-	-
Fuel tank (l)	130	130	130	260	350
Standard tires	500/70-R24	500/70-R24	500/70-R24	600/55-26.5	600/55-26.5
Operating weight (kg)	7800	7900	8400	8000	9500
Height (mm)	3070	3070	3070	3060	3070
Width (mm)	2470	2470	2470	2470	2470
Length (mm)	5518	5518	5518	5330	5690
3-point linkage capacity (kg)	2500	2500	2500	4500	4500
Mechanical PTO	○	○	○	-	-
Hydraulic power take off	●	●	●	●	●
Flow / pressure (l/min - bar)	150/350	150/350	150/350	285/420	500/420

CONCRETE MIXERS	DBM2500	DBM3500
Drum volume (l)	3500	5000
Concrete yield capacity (l)	2500	3500
Operating weight (kg)	7050	7400
Standard tires	405/70-20	500/45-20
Width (mm)	2300	2355
Height (mm)	2900	3100
Length (mm)	6220	6480
Max. unloading height (mm)	1760	2060
Water tank (l)	930	930
Bucket capacity (l)	700	700
Engine	Deutz TCD3.6	Deutz TCD3.6
Stage V	DOC+SCR+DPF	DOC+SCR+DPF
Displacement/Cylinders	3600/4	3600/4
Engine power (kW/HP)	74,4/100	74,4/100
EPD	●	●
Max. speed (km/h)	40	40
Drum rotation speed	0 ÷ 26	0 ÷ 18
ROPS	●	●
4WD and 4 steering wheel	●	●
Extension chute	2	2

TRACKED CARRIERS	CINGOM500	CINGOM700TD	CINGOM8.3TDEVO	CINGOM8.3EVO	CINGOM12.3EVO
Max. capacity (kg)	500	700	800	800	1200
Engine (HP)	Honda - 5,5 Stage V	Honda - 12 Stage II	Kubota - 17 Stage V	Kubota - 17 Stage V	Kubota - 21 Stage V
Fuel	Petrol	Petrol	Diesel	Diesel	Diesel
Electric starter	-	●	●	●	●
Max. speed (km/h)	3,5	2,5 - 4	4	4	5
Operating weight (kg)	230	480	510	510	720
Width (mm)	690	750	800	800	1000
Length (mm)	1471	1500	1750	1640	1830
Rubber track dimensions	160 x 72 x 33	180 x 72 x 36	180 x 72 x 36	180 x 72 x 36	230 x 72 x 40
Transmission control	Hydraulic	Hydraulic	Hydrostatic	Hydrostatic	Hydrostatic
Transmission pump (cc)	3,2 + 3,2	4,27 + 4,27	3 + 3	9 + 3	13 + 13
Gearmotors	-	●	●	●	●
Operator platform	-	●	●	●	●
Hydraulic pump (cc)	-	6	8 + 2,5	8 + 2,5	8 + 2,5
Flow / pressure (l/min - bar)	-	17/180	22+7/180	22+7/180	22+7/180
Oil radiator	-	●	●	●	●
Hydraulic outlet (in + out)	2	4	6 + 2	6 + 2	6 + 2
Multifunction with quick coupling	-	-	-	●	●

ROTATING TELEHANDLERS	ROTO40.16	ROTO40.16 S	ROTO40.18	ROTO40.18S	ROTO50.21	ROTO50.21S	ROTO50.21SPLUS	ROTO50.26	ROTO50.26S	ROTO50.26SPLUS	ROTO50.30S	ROTO50.30SPLUS	ROTO70.24S	ROTO70.24SPLUS	ROTO 50.35SPLUS CVTRONIC	ROTO 70.28SPLUS CVTRONIC
Max. capacity (kg)	4000	4000	4000	4000	4950	4950	4950	4950	4950	4950	4950	4950	7000	7000	4950	7000
Lifting height (m)	15,8	15,8	17,7	17,7	21	21	21	25,9	25,9	25,9	29,2	29,2	24,2	24,2	34	28
Operating weight (kg)	12900	13000	13500	13600	15800	15800	16500	16600	16600	17300	19800	20500	19500	20200	23350	22750
Standard tires	400/70-20	400/70-20	400/70-20	400/70-20	18-22.5	18-22.5	18-22.5	18-22.5	18-22.5	18-22.5	445/65 R22,5	445/65 R22,5	445/65 R22.5	445/65 R22.5	445/80 R 25	445/80 R 25
Width (mm)	2100	2310	2240	2240	2430	2430	2430	2430	2430	2430	2490	2490	2490	2490	2540	

